



Product Service

CERTIFICATE

No. Z1A 090361 0031 Rev. 00

Holder of Certificate: **Kinnarps AB**

Industrigatan 1
521 88 Kinnarp
SWEDEN

Certification Mark:



Product:

Office Desks
Sit-/ standing desk tables

Tested according to:

EK5/AK3 13-01:2018
DIN EN 527-1:2011
DIN EN 527-2:2019
DIN-Fachbericht 147:2006
AfPS GS 2019:01 PAK

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713202884

Valid until: 2026-11-25

Date, 2021-11-29

(Jens Biesenack)

CERTIFICATE

No. Z1A 090361 0031 Rev. 00

Model(s):

Table System Oberon

Model-no.

OB1212D, OB1210, OB1288, OB814, OB816, OB1016, OB1018, OB1020, OB1216, OB1218K, OB1220, OB1221K, OB8816, OB84, OB104, OB68, OB88, OB108, OB128, OB148, OB168, OB188, OB208, OB66, OB86, OB106, OB126, OB146, OB166, OB6125, OB127, OB147, OB167, OB187, OB148A, OB168A, OB188A, OB208A, OB149A, OB169A, OB189A, OB209A, OB1809E

Parameters:

Height adjustable (SS/SSA)	Sit/stand desks (SS round legs/SSA square legs) are variably height adjustable with press of a button. The desk height is between 620 and 1270 mm.
Sit/stand adjustable legs (SM/SMA)	The manually adjustable legs (SM round/SMA square) for sedentary work are to customize for different users. With a crank the tabletop is raised and lowered. The adjustable height range is between 620 and 1270 mm. Legs with a fixed height of 740 mm (SF) are available for all tables.
Tabletop	Thickness: 22 mm
	Chipboard with wood and a solid wood lipping or laminated
Underframe	Powder-coated dual-function beam with T-slot. Beams separate color, brackets and legs are the same color.
	T-frame consisting of powder-coated steel
	SS/SSA: 72/66/60 mm
	SM/SMA: 70/60 mm
	SF/SFA: 70 mm
Foot	In aluminium or steel
	With concealed adjustment screw for uneven floors (0-10 mm)

CERTIFICATE

No. Z1A 090361 0031 Rev. 00

Product overview table system Oberon:

Product name	Dimension Length x Depth	Model-no.
Table 1212D For connection on 1 or both sides	1200 x 600 mm	OB1212D Freestanding Connected 1 side (2 legs) Connected on both (1 leg)
Table 1210 For connection on 1 or both sides	600/1000 x 1200/800 mm	OB1210 Edge 1 connected (2 legs) Edge 2 connected (1 leg) Connected on both (1 leg)
Table 1288 For connection on 1 or both sides	800/1200 x 1200/800 mm	OB1288 Edge 1 connected (2 legs) Edge 2 connected (1 leg) Connected on both (1 leg)
Table 814 Freestanding or for connection on 1 or both sides	1400/400 x 800/600 mm	OB814 Freestanding Edge 1 connected (2 legs) Edge 2 connected (1 leg) Connected on both (1 leg)
Table 816 Freestanding or for connection on 1 or both sides	1600/400 x 800/600 mm	OB816 Freestanding Edge 1 connected (2 legs) Edge 2 connected (1 leg) Connected on both (1 leg)
Table 1016 Freestanding or for connection on 1 or both sides	1600/400 x 1000/800 mm	OB1016 Freestanding Edge 1 connected (2 legs) Edge 2 connected (1 leg) Connected on both (1 leg)
Table 1018 Freestanding or for connection on 1 or both sides	1800/400 x 1000/800 mm	OB1018 Freestanding Edge 1 connected (2 legs) Edge 2 connected (1 leg) Connected on both (1 leg)
Table 1020 Freestanding or for connection on 1 or both sides	2000/400 x 1000/800 mm	OB1020 Freestanding Edge 1 connected (2 legs) Edge 2 connected (1 leg) Connected on both (1 leg)
Table 1216 Freestanding or for connection on 1 or both sides	1600/600 x 1200/800 mm	OB1216 Freestanding Edge 1 connected (2 legs) Edge 2 connected (1 leg) Connected on both (1 leg)
Table 1218K Freestanding or for connection on 1 or both sides	1800/600 x 1200/800 mm	OB1218K Freestanding Edge 1 connected (2 legs) Edge 2 connected (1 leg) Connected on both (1 leg)

CERTIFICATE

No. Z1A 090361 0031 Rev. 00

Product name	Dimension Length x Depth	Model-no.
Table 1220 Freestanding or for connection on 1 or both sides	2000/600 x 1200/800 mm	OB1220 Freestanding Edge 1 connected (2 legs) Edge 2 connected (1 leg) Connected on both (1 leg)
Table 1221K Freestanding or for connection on 1 side	2100/600 x 1200 mm	OB1221K Freestanding Connected on 1 side (2 legs)
Table 8816 Freestanding or for connection on 1 or both sides	1600/600 x 800 mm	OB8816 Freestanding Edge 1 connected (2 legs) Edge 2 connected (1 leg)
Table 84 For connection on 1 side	800 x 400 mm	OB84 Connected 1 side
Table 104 For connection on 1 side	1000 x 400 mm	OB104 Connected 1 side
Table 68 For connection on 1 or both sides	600 x 800 mm	OB68 Connected 1 side Connected on both
Table 88 Freestanding or for connection on 1 or both sides	800 x 800 mm	OB88 Freestanding Connected 1 side Connected on both
Table 108 Freestanding or for connection on 1 side	1000 x 800 mm	OB108 Freestanding Connected 1 side
Table 128 Freestanding or for connection on 1 side	1200 x 800 mm	OB128 Freestanding Connected 1 side
Table 148 Freestanding or for connection on 1 side	1400 x 800 mm	OB148 Freestanding Connected 1 side
Table 168 Freestanding or for connection on 1 side	1600 x 800 mm	OB168 Freestanding Connected 1 side
Table 188 Freestanding or for connection on 1 side	1800 x 800 mm	OB188 Freestanding Connected 1 side
Table 208 Freestanding or for connection on 1 side	2000 x 800 mm	OB208 Freestanding Connected 1 side
Table 66 Connection on 1 side only	600 x 600 mm	OB66 Connected 1 side
Table 86 Freestanding or connection on 1 side	800 x 600 mm	OB86 Freestanding Connected 1 side
Table 106 Freestanding or connection on 1 side	1000 x 600 mm	OB106 Freestanding Connected 1 side

CERTIFICATE

No. Z1A 090361 0031 Rev. 00

Product name	Dimension Length x Depth	Model-no.
Table 126 Freestanding or connection on 1 side	1200 x 600 mm	OB126 Freestanding, connected 1 side
Table 146 Freestanding or connection on 1 side	1400 x 600 mm	OB146 Freestanding, connected 1 side
Table 166 Freestanding or connection on 1 side	1600 x 600 mm	OB166 Freestanding, connected 1 side
Table 127 Freestanding or connection on 1 side	1200 x 700 mm	OB127 Freestanding, connected 1 side
Table 147 Freestanding or connection on 1 side	1400 x 700 mm	OB147 Freestanding, connected 1 side
Table 167 Freestanding or connection on 1 side	1600 x 700 mm	OB167 Freestanding, connected 1 side
Table 187 Freestanding or connection on 1 side	1800 x 700 mm	OB187 Freestanding, connected 1 side
Table 6125	1250 x 600 mm	OB6125 Freestanding or: connected 1 side outlet 1 or 3 connected 2 sides outlet 1 or 3 or: 1 edged connected outlet 2
Table 148A Freestanding or connection on 1 side	1400 x 800 mm	OB148A Freestanding, connected 1 side
Table 168A Freestanding or connection on 1 side	1600 x 800 mm	OB168A Freestanding, connected 1 side
Table 188A Freestanding or connection on 1 side	1800 x 800 mm	OB188A Freestanding, connected 1 side
Table 208A Freestanding or connection on 1 side	2000 x 800 mm	OB208A Freestanding, connected 1 side
Table 149A Freestanding or connection on 1 side	1400 x 900 mm	OB149A Freestanding, connected 1 side
Table 169A Freestanding or connection on 1 side	1600 x 900 mm	OB169A Freestanding, connected 1 side
Table 189A Freestanding or connection on 1 side	1800 x 900 mm	OB189A Freestanding, connected 1 side
Table 209A Freestanding or connection on 1 side	2000 x 900 mm	OB209A Freestanding, connected 1 side
Table 1809E Freestanding	1800 x 900 mm	OB1809E Freestanding